

BASIC LOCAL EXCHANGE SERVICE

3.8 DIRECT INWARD DIALING SERVICE (Cont'd)

3.8.1. General (Cont'd)

- G. Customer-premises switching systems must be able to intercept unused numbers transmitted to the switching equipment.
- H. DID Service telephone numbers are normally provided in blocks of twenty (20) consecutive numbers. However, the blocks may be provided on a nonconsecutive basis subject to the technical configuration of the serving central office. The Cooperative retains its rights to the telephone numbers used in DID service. Subscribers who originally received DID Service telephone numbers in blocks of one hundred (100) prior to the effective date of this tariff, are grandfathered from this change in the DID block configuration. (C)
(C)
(C)
|
(C)
- I. Subscribers to DID service will be required to maintain an adequate number of DID trunks as determined by the Cooperative in order to provide a "quality" grade of service and prevent network degradation.

3.8.2 Rates and Charges

A. Central Office Components

	<u>Installation Charge</u>	<u>Monthly Charge</u>	<u>Tariff Code</u>	
(1) Establish trunk group and provide group of 20 DID numbers	\$300.00	\$ 4.00	D7	(C) (R)
(2) Each additional group of 20 DID numbers	\$100.00	\$ 4.00	D8	(C) (R)
(3) DID Trunk Termination	\$ 50.00	\$49.50	D9	

ISDN SERVICES

Table of Contents

11.1	ISDN-BASIC RATE INTERFACE SERVICE	Sheet No.	
11.1.1	General	2	
11.1.2	Abbreviations	3	
11.1.3	Service Components	4	
11.1.4	Rules and Regulations	10	
11.1.5	Rates and Charges	14	
11.2	ISDN-PRIMARY RATE INTERFACE SERVICE		(N)
11.2.1	General	18	
11.2.2	Rules and Regulations	19	
11.2.3	Rates and Charges	20	(N)

ISDN SERVICES

11.2 ISDN-PRIMARY RATE INTERFACE SERVICE

(N)

11.2.1 General

- A. Integrated Service Digital Network (ISDN) – Primary Rate Interface (PRI) is a central office based service arrangement that can be utilized for the customer for the transport of various individual access services.
- B. ISDN-PRI is provisioned as a clear channel 1.544 megabit per second (Mbps) facility and uses the ISDN architecture of 23 “B” (Bearer) channels and one “D” (Delta) channel or 24 additional “B” channels (each additional arrangement must have at least one “D” channel). This facility will provide the customer with a capable element for simultaneous access, transmission and switching of voice, data and imaging traffic via channelized transport.
- C. B channel – a bi-directional synchronous channel capable of digital transmission speeds of 64 kilobits per second (kbps). Each individual “B” channel can be configured to transport circuit-switched voice, circuit-switched data, or alternate circuit-switched voice/data traffic types.
- D. D Channel – the single 64kbps channel on the facility that provides signaling and control functions for the “B” channels. One “D” channel can control up to five (5) PRI trunks of which one trunk would contain the “D” channel and 23 “B” channels while the other trunks would be provisioned with 24 “B” channels.
- E. This Tariff provides for PRI switching capabilities only. Additional services, if desired, must be subscribed to under other sections of this Tariff. Each ISDN-PRI trunk group will be provided with one telephone number. Additional numbers or DID service may be purchased as specified elsewhere in this Tariff.

(N)

ISDN SERVICES

11.2 ISDN-PRIMARY RATE INTERFACE SERVICE

(N)

11.2.2 Rules and Regulations

- A. The regulations and rates expressed herein are in addition to all applicable regulations and rates specified in other sections of this tariff unless otherwise specified. ISDN-PRI as provided for in this Tariff, is only to be used in the provisioning of a user-to network interface.
- B. ISDN-PRI service is furnished at the option of the Cooperative. These services are furnished subject to central office switching capability, capacity, and the availability of outside plant facilities meeting the criterion for ISDN-PRI service.
- C. Customer Premise Equipment (CPE) compatibility is the responsibility of the user. CPE must be compliant with the NI-2 specification. Any exception or deviation requiring custom switch features that are not NI-2 compliant will be supported as an exception, solely at the discretion of the Cooperative and will be priced on an individual case basis.
- D. The Cooperative shall not be held responsible to the customer if any changes in equipment, operations, or procedures of the Cooperative render the CPE obsolete or requiring modification or alteration or otherwise affect its use or performance.
- E. This Tariff does not provide for the transmission of packet data on the "B" or "D" channels.
- F. ISDN-PRI Access is offered for a minimum contract period of one year. Early termination liability charges shall be equal to the monthly access rate times the number of months remaining in the contract.
- G. ISDN-PRI service is not available to Commercial Radio Mobile Carriers, Private Mobile Radio Carriers and Interexchange Carriers in their provision of services to their customers.

(N)

