

ACCESS SERVICE

CHECK SHEET (Cont'd)

<u>Page</u>	<u>Revision</u>	<u>Page</u>	<u>Revision</u>	<u>Page</u>	<u>Revision</u>
8-27	Original	8-61	Original	9-27	Original
8-28	Original	8-62	Original	9-28	Original
8-29	Original	8-63	Original	9-29	Original
8-30	Original	8-64	Original	9-30	Original
8-31	Original	8-65	Original	9-31	2nd
8-32	Original	8-66	Original	9-32	2nd
8-33	Original	8-67	Original	9-33	2nd
8-34	Original	8-68	Original	9-34	Original
8-35	Original	9-1	Original	9-35	Original
8-36	Original	9-2	Original	9-36	1st*
8-37	Original	9-3	Original	9-37	Original
8-38	Original	9-4	1st	9-38	2nd
8-39	Original	9-5	1st	9-39	1st
8-40	Original	9-6	Original	9-40	Original
8-41	Original	9-7	Original	9-41	2nd
8-42	Original	9-8	Original	9-42	1st
8-43	Original	9-9	1st	9-43	2nd
8-44	Original	9-10	Original	9-44	2nd
8-45	Original	9-11	Original	9-45	1st
8-46	Original	9-12	Original	9-46	1st
8-47	Original	9-13	Original	9-47	Original
8-48	Original	9-14	Original	9-48	2nd
8-49	Original	9-15	Original	9-49	Original
8-50	Original	9-16	Original	9-50	Original
8-51	Original	9-17	Original	9-51	1st
8-52	Original	9-18	Original	9-52	1st
8-53	Original	9-19	Original	9-53	Original
8-54	Original	9-20	Original	9-54	2nd
8-55	Original	9-21	Original	9-55	Original
8-56	Original	9-22	Original	9-56	Original
8-57	Original	9-23	Original	9-57	Original
8-58	Original	9-24	Original	9-58	Original
8-59	Original	9-25	Original		
8-60	Original	9-26	Original		

*Issued January 21, 2014

Issued: January 21, 2014

Effective: February 18, 2014

HTC Communications, Inc.
3480 Highway 701 North
Conway, SC 29528

ACCESS SERVICE

9. SPECIAL ACCESS SERVICE (Cont'd)

9.6 Voice Grade Service (Cont'd)

9.6.3 Optional Features and Functions (Cont'd)

9.6.3.C Conditioning (Cont'd)

9.6.3.C(3) Telephoto Capability

Telephoto Capability provides transmission characteristics suitable for telephotographic communications. Specifically, Telephoto Capability is provided for the control of attenuation distortion and envelope delay distortion on telephotographic services. The attenuation distortion and envelope delay distortion parameters for Telephoto Capability are delineated in Technical Reference TR-TSY-000335. The rate for this option is set forth in 12.6.4(C)(2) following.

9.6.3.C(4) Sealing Current Conditioning

Sealing Current Conditioning is provided to help maintain continuity on dry metallic loops.

T

9.6.3.D Customer Specified Premises Receive Level

This option allows the customer to specify the receive level at the Point of Termination. The level must be within a specific range on effective four-wire transmission. The ranges are delineated in Technical Reference TR-TSY-000335. The rate for this option is set forth in 12.6.4(C)(4) following.